



F.P. JOURNE  
Invenit et Fecit

OCTA DIVINE



**OCTA DIVINE**  
NEW INTERPRETATION OF THE EMBLEMATIC OCTA COLLECTION

**After the Chronomètre Optimum, the Quantième Perpétuel and the Octa Lune,  
it is the turn of the Octa Divine to move onto size 42 mm.**

Completely redesigned in 42mm, F.P. Journe's Octa Divine model now features a new look: elegant, uncluttered, and perfectly legible.

The instantaneous large date is displayed in enlarged windows that stand out against the Gold dial where the seconds disk display and the power reserve indicator are subtly delineated.

The elegant sapphire moon phase disk, the delicate blued steel hands, and the streamlined polished steel circle screwed to the dial are all exclusive characteristics of F.P. Journe.

A spark of whimsy is added by the different sized numerals of the hours ring, while red dots enliven the resolutely contemporary aesthetics of the dial.

The movement of the Octa Divine (calibre 1300.3), manufactured in 18K rose Gold, is automatically wound and has a power reserve of over 5 days. The unidirectional winding of the exclusive off-centre F.P. Journe rotor in 22K red Gold is achieved by a self-locking ball bearing system. Thus each movement, no matter how slight, is utilised for the optimal winding of the watch.

The Octa Divine, available in the F.P. Journe Boutiques, also exists with a 40 mm case, in Platinum or in 18K red Gold.

## Specifications\_

---

### Movement\_

Exclusive FPJ calibre 1300.3 in 18K rose Gold.  
Mechanism with unidirectional automatic winding  
Rotor in 22K red Gold, off centre and guilloché

---

### Dimensions of the movement\_

Overall diameter: 30.80mm  
Casing-up diameter: 30.40 mm  
Overall height: 5.70 mm  
Height of winding system: 3.00 mm  
Diameter of stem thread: S0.90 mm

---

### Balance\_

Chronometric, with 4 inertia weights  
Flat Anachron microflamed spring  
Mobile stud holder  
Free sprung balance  
Nivatronic laser-welded to collet  
Pinned GE stud  
Frequency: 21,600v/h (3Hz)  
Inertia: 10.10 mg\*cm<sup>2</sup>  
Angle of lift: 52°  
Amplitude: 12h dial up: >280° - 90h dial up: >220°

---

### Autonomy\_

160 ± 12 heures  
Winding speed: 274 rotations (anti clock wise) / 24 hours

---

### Main Characteristics\_

Three position crown  
Winding of the watch, position 0, clock wise  
Correction of the date, position 1, anti clock wise,  
Correction of the moon, position 1, clock wise,  
Correction of the time, position 2  
Instantaneous date change  
Barell with slipping spring  
In line lever escapement, 15 tooth wheel

---

### Indications\_

Central hours and minutes, small second in window at 4h30  
Large date in window at 11h30  
Power reserve at 10h00  
Phases of the moon 7h30

---

### Finishing\_

Circular Côtes de Genève on bridges  
Partial circular graining on base plate  
Polished screw heads with chamfered slots  
Pegs with polished rounded ends  
Steel components hand polished and chamfered

---

### Case\_

Platinum PT 950 or 18K red Gold  
Diameter: 40 or 42 mm  
Total height: 10.6 mm

---

### Number of parts\_

Jewels: 37  
Movement without dial: 281  
Cased up on leather strap: 321





Calibre 1300.3  
automatic winding