

Specifications

MOVEMENT	
	Calibre 1505
	Manually wound
	Gold baseplate and bridges
	40 jewels

MOVEMENT DIMENSIONS		
	Overall diameter:	35.80mm
	Casing diameter :	35.00mm
	Frame height :	6.25mm
	Overall height:	7.80mm
	Height of stem axis:	3.41mm
	Stem-thread diameter:	S1.20mm

BALANCE		
	Free - sprung	
	4 adjustment weights	
	Flat Anachron balance-spring	
	Fixed stud-holder	
	Pinned stud	
	Spring pinned to the collet	
	Frequency:	21,600 v/h (3Hz)
	Inertia:	11.00 mg/cm²
	Angle of lift:	52°
	Amplitude:	Dial up, fully wound: > 340°
		Dial up, 24 hours: > 300°

ESCAPEMENT	
	Linear escapement
	15 -tooth escape-wheel

VISUAL INDICATIONS	
	Hours and minutes, off-centre
	Small seconds at 6 o'clock
	Power reserve
	Strike mode selection
	Striking hammers

SOUND INDICATIONS	
	Grand strike, small strike on the quarters in passing
	Strike silent
	Minute-repeater on demand

AUTONOMY	
	120 hours without chime
	Approx. 48 hours with grand strike
	Approx. 24 hours after strike runs down

FINISH	
	Circular grained baseplates
	Circular ribbing on the bridges
	Polished and bevelled screws
	Pegs with rounded, polished ends
	Steelwork decorated by hand
	3D engraving

CASE		
	Steel	
	Diameter:	42.00mm
	Overall height:	12.25mm

CONTROLS	
	Two position winding and setting crown
	Pushbutton to release the minute-repeater at 2 o'clock
	Pushbutton to select the strike mode at 4 o'clock

NUMBER OF PIECES		
	Movements without dial	408
	Cased-up, on leather	441
	Cased-up, steel bracelet	558